



## 产品特性/Product Features

- IP6K9K
- 350A 85°C长时间载流能力
- 12-750VDC
- 1000MΩ (1000VDC) , IEC 60664-1
- PWM
- 
- 
- 

### 触点参数 / Contact parameters

		1a	
		0.5m at 350A	
		350A	
		2×10 <sup>5</sup>	
		<b>450型</b>	<b>750型</b>
		750VDC	750VDC
		2000A 320VDC 1	2000A 320VDC 1
		135kW	225kW
1		5×10 <sup>4</sup> 32VDC, =1ms, 350A	5×10 <sup>4</sup> 32VDC, =1ms, 350A
		50 64VDC, =1ms, 650A	50 64VDC, =1ms, 650A
		1×10 <sup>3</sup> 450VDC, 350A	500 750VDC, 350A
		200 450VDC, -350A	100 750VDC, -350A
		1 450VDC, 2000A	1 450VDC, 2000A
z		350A:	
		450A:10min	
		600A:1min	
		2000A:1s	
辅助 接点	Ue	1NO	
		30VDC/125VAC	
		2A DC /3A AC	
		9V0.1A	

1) 23°C, 0.6s:5.4s.

2) 85°C, 150mm<sup>2</sup>, " "

Drilling hole size

/Unit mm

性能曲线图 Performance graph

